





3, Table 2 General characteristics

Rated Vol. (V)	A Derated Vol. 125 (V)	B Derated Vol. 200 (V)	Nominal Cap. (F)	Dissipation Factor +25 +85 +200 (%)	Leakage current (A)		Impedance 100Hz -55 ()	Cap change rate (%)			85 40KHZ AC Ripple current (mA)	Case Code					
					+25	+85 +125		-55	+85	+200							
6	4	3.6	30	7	1	2	100	-40	+11	+15	820	T1					
			68	12			60				+14		+18	960			
			140	17			40						+20	1200			
			270	30	2	7	25	-44	+18	+25	1375	T2					
			330	30			20				+14		+20	1800			
			560	45			13				25		-64	+18	+25	1900	T3
			1200	90			3				14		20	-80	+25	+30	
8	5	4.8	25	7	1	2	100	-40	+11	+15	820	T1					
			56	10			59				+14		+18	900			
			120	15			50						+18	+20	1220		
			220	30	7	30	-44	+25	1370	T2							
			290	30	2	6			25		-64	+18		1770			
			430	36		14	25	1825									
			850	50	4	16	22	-80	+25	+30	2330	T4					
10	7	6	20	5	1	2	175	-32	+11	+15	820	T1					
			47	11			100				+14		+18	855			
			100	12			60						-36	+20	1200		
			180	20	7	40	+25	1365									
			250	25	2	10		30	-40	+18	1720	T3					
			390	25		16	25	-64			1800						
			750	40	4	23	-80	+25	+30	2360	T4						

Please read the important notes and cautions at the end of this document.



Table 2 General characteristics

Rated Vol. (V)	A Derated Vol. 125 (V)	B Derated Vol. 200 (V)	Nominal Cap. (F)	Dissipation Factor +25 +85 +200 (%)	Leakage current (A)		Impedance 100Hz -55 ()	Cap change rate (%)			85 40KHZ AC Ripple current (mA)	Case Code	
					+25	+85 +125		-55	+85	+200			
30	20	18	8	4	1	2	275	-16	+8	+12	640	T1	
			15	5			175	-20	+11	+15	780		
			40	8			65	-24			1120	T2	
			68	11	8	60	+13	1285					
			100	15	2	10	40	-28	+11	+18	1450	T3	
			150	20		15	35	-48	+13	+25	1525		
			300	25	8	32	25	-60	+25	+35	1950	T4	
50	30	30	5	3	1	2	400	-16	+5	+9	580	T1	
			10	4			250	-24	+8	+12	715		
			25	7			95	-20	+11	+15	1005	T2	
			47	10	8	70	-28	+13	+18	1155			
			60	10	2	10	45	-16	+11	+15	1335	T3	
			82	12		12	45	-32	+13	+18	1400		
			160	15	8	30	27	-50	+25	+30	1900	T4	
60	40	36	4	2.8	1	2	550	-16	+5	+9	525	T1	
			8.2	4			275	-24	+8	+12	625		
			20	6			105	-16	+11	+15	930	T2	
			39	8	90	-28	1110						
			50	9	2	10	50	-16	+11	+15	1330	T3	
			68	10		10	45	-32			1365		
			140	12	8	30	28	-40	+20	+25	1850	T4	
			*560	50	30	160	25	-60	+40	+50	2800	T5	
75	50	45	3.5	2.5	1	2	650	-16	+5	+9	525	T1	
			6.8	3.5			300	-20	+8	+12	610		
			15	5			150	-16	+11	+18	890	T2	
			33	8	90	-24	1000						
			40	8	2	10	60	-16	+11	+15	1250	T3	
			56	10		12	60	-28			+18		1335
100	65	60	110	10	9	30	29	-35	+20	+25	1850	T4	
			2.5	2	1	2	950	-16	+7	+10	505	T1	
			4.7	3							500		-20
			11	5							4	200	-16
			22	6	9	100	-24	965					

Please read the important notes and cautions at the end of this document.

